

# FENCE WEAVE®



**Fence Weave® has been enhancing chain link fence since 1963.**

As an attractive companion for chain link fence, Fence Weave is a natural fit for homeowners who would like to do it themselves. Its unique packaging is easy to display in retail and home improvement centers.

### Design

Fence Weave is produced with flexible, durable polyethylene (LDPE). Fence Weave comes in (9) standard colors listed below.

### Standard Heights & Size

Fence Weave is Width 1.875" x Thickness .024" x Length. Each roll is 250' long and covers 40 square feet of fence.

### Fence Weave Roll Calculator

To determine how many rolls are needed follow this easy formula: Height of Fence x Length of Fence divided by 40 = # of rolls of Fence Weave (example: 4' x 50' / 40 = 5 rolls).

### Wind Load & Privacy Factor

Approximately 75%.

### Colors\*



Special colors are available upon request - minimum order quantities apply.

\* Exact representation of slat colors in printing is difficult. Please refer to actual color samples for final matching. Covered by one or more of the following patents: US Patent 6,068,243 / 5,165,664 / 5,234,199



**FENCE PRODUCTS**

*PDS® is a registered trademark of Pexco.*

**Made in the USA**





# PRODUCT SPECIFICATIONS

Slat Type	Slat Width	Mesh Size	Wire Gauge	Slats Per Bag	Approx. Coverage Per Box
Fence Weave®	1 7/8"	2", 2 1/4" or 2 3/8"	9, 11, 11 1/2 or 12 1/2	-	40 square feet

## Materials

The Fence Weave product is extruded from Low Density Polyethylene (LDPE), color pigments and ultra violet (UV) inhibitors, specifically designed to retard the harmful effects of the sun and lengthen the life of the product.

## Durability

Pexco PDS® LDPE Fence Products are resistant to: severe weather conditions, salt water, sand, road dirt, most acids, alcohol, alkaline, ammonia, petroleum distillates, and common environmental pollutants.

## Maintenance

Pressure cleaning of surface contaminants is quickly accomplished with plain water.

## Wind Load Disclaimer

Pexco will not be responsible for damage due to wind load conditions resulting from insufficient structural support.

## Installation Instructions

Simply weave into chain link fence, cut and fasten with provided solid brass fasteners.

## Limited Warranty

Fence Weave carries a 5-year, pro-rata warranty against breakage under normal conditions. Write Pexco for full warranty information.

## Packaging

Each Fence Weave roll comes in a full color box. Includes 125 solid brass fasteners and installation instructions.



**FENCE PRODUCTS**

## LDPE Technical Properties

Property	Value
Melt Index	(1.5) Optimum extrusion processing conditions for Fence Slats
Density	(.92) Polyethylene ranges anywhere from .914 to .960 in density
Minimum Temp.	(-30°) Under no stress, LDPE remains flexible at this temperature
Maximum Temp.	(160°) Under no stress, LDPE will not distort at this temperature
Tensile Strength	(1,450 psi) LDPE will not distort at lesser loads or impacts

## PEXCO LLC

Tacoma, WA 98424 | Athol, MA 01331  
800.822.SLAT (7528) | 800.755.SLAT (7528)

## VISIT US AT:

[www.pexco.com/fence](http://www.pexco.com/fence)

## EMAIL US AT:

[fence.sales@pexco.com](mailto:fence.sales@pexco.com)

Contact your local fence professional for more information about our complete line of enhancement products.

