

FIN2000® PRE-WOVEN (Extra-Privacy)



When you need extra privacy for commercial or industrial applications, our Fin2000® Pre-Woven Slat is the answer.

This uniquely styled slat is mechanically inserted into the chain link wire during the weaving process. Once inserted, the wire is finished above and below the slat (either bow-knuckle or knuckle-over).

Design

FIN2000® Pre-Woven Slats are flat and tubular in shape, with two “legs” inside the rigid, hollow body of the slat, for extra support. These slats also have strong unique fins positioned on each side of the slat body, for extra screening and security.

Standard Heights

4, 5, 6, 7, 8, 10 & 12 feet. Special heights available upon request.

Wind Load & Privacy Factor

Approximately 90%.

Upon Special Request

Available in bags that cover 25 linear feet for smaller jobs.

SLAT PROFILE:



Colors*



* Exact representation of slat colors in printing is difficult. Please refer to actual color samples for final matching. Covered by one or more of the following patents: US Patent 6,068,243 / 5,165,664 / 5,234,199



FENCE PRODUCTS

PDS® is a registered trademark of Pexco.

Made in the USA





PRODUCT SPECIFICATIONS

Slat Type	Slat Width	Mesh Size	Wire Gauge	Slats Per Crate	Approx. Coverage Per Crate
Fin2000®	2 ^{13/16}	3 ^{1/2} " x 5"	9 or 10	2,544 (106 pieces/bag)	600 linear feet (25 linear feet/bag)

Materials

The Fin2000 Pre-Woven product is extruded from High Density Polyethylene (HDPE), color pigments and ultra violet (UV) inhibitors, specifically designed to retard the harmful effects of the sun and lengthen the life of the product.

Durability

Pexco PDS® HDPE Fence Products are resistant to: severe weather conditions, salt water, sand, road dirt, most acids, alcohol, alkaline, ammonia, petroleum distillates, and common environmental pollutants.

Maintenance

Pressure cleaning of surface contaminants is quickly accomplished with plain water.

Wind Load Disclaimer

Pexco will not be responsible for damage due to wind load conditions resulting from insufficient structural support.

Limited Warranty

Fin2000 Pre-Woven carries a 25-year, pro-rata warranty against breakage under normal conditions. Write Pexco for full warranty information.

Installation Instructions

Because this slat comes pre-inserted in the chain link fabric, just stretch the wire and tie it up. The result is a fully slatted fence with 90% privacy.

Note

Pexco is the manufacturer of the plastic slats only, we do not weave the wire. For pre-woven products, please contact your fence supplier or contact us for a supplier near you.



HDPE Technical Properties

Property	Value
Melt Index	(.35) Optimum extrusion processing conditions for Fence Slats
Density	(.945) Polyethylene ranges anywhere from .914 to .960 in density
Minimum Temp.	(-70°) Under no stress, HDPE remains flexible at this temperature
Maximum Temp.	(180°) Under no stress, HDPE will not distort at this temperature
Tensile Strength	(3,700 psi) HDPE will not distort at lesser loads or impacts

PEXCO LLC

Tacoma, WA 98424 | Athol, MA 01331
800.822.SLAT (7528) | 800.755.SLAT (7528)

VISIT US AT:

www.pexco.com/fence

EMAIL US AT:

fence.sales@pexco.com

Contact your local fence professional for more information about our complete line of enhancement products.

