

# PEXCO



## FENCE WEAVE



### Specifications

**Design:** Fence Weave is produced with flexible, durable polyethylene (LDPE). Fence Weave comes in (9) standard colors listed below.

**Standard Heights:** Fence Weave is Width 1.875" x Thickness .024" x Length. Each roll is 250' long and covers 40 square feet of fence.

**Wind Load & Privacy Factor:**  
Approximately 75%

**Fence Weave Roll Calculator:** To determine how many rolls are needed follow this easy formula:  
Height of Fence x Length of Fence divided by 40 = # of rolls of Fence Weave  
(Example: 4' x 50' / 40 = 5 rolls).



Fence Weave® has been enhancing chain link fence since 1963.

As an attractive companion for chain link fence, Fence Weave is a natural fit for homeowners who would like to do it themselves. Its unique packaging is easy to display in retail and home improvement centers.

COLORS:\*

Black

White

Gray

Beige

Brown

Redwood

Green

Royal Blue

Light Blue

SPECIAL COLORS ARE AVAILABLE UPON REQUEST - MINIMUM ORDER QUANTITIES APPLY.

SLAT TYPE	SLAT WIDTH	MESH SIZE	WIRE GAUGE	SLATS PER BAG	APPROX. COVERAGE PER BOX
Fence Weave®	1 7/8"	2", 2 1/4", or 2 3/8"	9, 11, 11 1/2, or 12 1/2	-	40 square feet

## QUALITY MATERIALS

The Fence Weave product is extruded from Low Density Polyethylene (LDPE), color pigments, and ultra violet (UV) inhibitors, specifically designed to retard the harmful effects of the sun and lengthen the life of the product.

## HIGH DURABILITY

Pexco PDS® LDPE Fence Products are resistant to severe weather conditions, salt water, sand, road dirt, most acids, alcohol, alkaline, ammonia, petroleum distillates, and common environmental pollutants.

## EASY MAINTENANCE


Pressure cleaning of surface contaminants is quickly accomplished with plain water.



## INSTALLATION INSTRUCTIONS



**STEP 1:** Simply weave into chain link fence, cut, and fasten with provided solid brass fasteners.



## LDPE TECHNICAL PROPERTIES

### Melt Index

(1.5) Optimum extrusion processing conditions for Fence Slats

### Density

(.92) Polyethylene ranges anywhere from .914 to .960 in density

### Minimum Temp.

(-30°) Under no stress, LDPE remains flexible at this temperature

### Maximum Temp.

(160°) Under no stress, LDPE will not distort at this temperature

### Tensile Strength

(1,450 psi) LDPE will not distort at lesser loads or impacts

\* Exact representation of slat colors in printing is difficult. Please refer to actual color samples for final matching.

Covered by one or more of the following patents: US Patent **6,068,243 / 5,165,664 / 5,234,199**

\*\* Fence Weave carries a 5-year, pro-rata warranty against breakage under normal conditions. Write Pexco for full warranty information.

Wind Load Disclaimer: Pexco will not be responsible for damage due to wind load conditions resulting from insufficient structural support.

Tacoma, WA 98424 // Athol, MA 01331

PHONE 800.755.SLAT (7528) / EMAIL [fence.sales@pexco.com](mailto:fence.sales@pexco.com)

**PEXCO.COM**